



KALYANI INDUSTRIES

Supply & Mfg of Industrial Electronic & Instrumentation Items

401, Palaj Heights, Vrundavan Nagar, Vikhe Patil School
Road, Kamatwade, Nashik - 422008

8888865647,8805464348,Kalyani.industries@rediffmail.com

QUOTATION

Subject: Humidity Controller & RTD +RH sensor

1. Humidity – Temperature Indicator/ Controller		
PARAMETER	MODEL	PRICE
<u>Humidity Indicator - Dual Alarm Relay Output</u> Input : RH SENSOR [Pls specify type] OP1 : OP2 : SSR or Rly [Please specify , factory set]	Hi-100 48x48	Rs.2,225 Extra : 72x72, 96x96 , 48x96 : Rs.165
<u>Composite Humidity – Temp. Indicator/ On-off Controller</u> Version 1 : Input : Dry WET Rtd Assembly Version 2 : Input : Rtd & rh 0-3.3 vdc / 1-3.6 vdc . 0-1 vdc OP1 : OP2 : Rly	Humitherm – i On-off version 48x48	Rs.5,335 Extra : RS485 : Rs.500
<u>Composite Humidity – Temp. Indicator with Alarms</u> Input : Universal Transmitter Excitation Voltage : + 12vdc & 5 vdc Output 3 : Temperature Alarm : Settable Relay NO/C or SSR Output 4 : Humidity Alarm : Settable Relay NO/C or SSR Optional : 24vdc Transmitter Extn. Voltage Op 1 : Temp. Control : On-off : Relay NO/C or SSR Op2 : Humidity Control : On-off : Relay NO/C or SSR Op5 : Temp.Retransmission PV : 4-20MAor 0-5/10 vdc Op6 : Humidity Retransmission PV : 4-20MAor 0-5/10 vdc RS485 : Serial Communication port, Modbus RTU protocol	Humitherm – i On-off version 96X96	Rs.7,555 Extra : Rs.300 each for all optional outputs/features

Cont...
....2

NO	DESCRIPTION	QTY	DISCOUNTED LIST PRICE
2. RTD + RH Sensor			
A]	RTD PT100 Temperature sensor Transition Joint Type [HSN Code – 90278030] Configuration : Simplex Range : -20 to +250 deg.c Accuracy : Class "A" MOC : SS316 Stem Size : 4 mm dia , 2.5" length Cable : 3 Mtr Teflon/ Teflon	01 No.	Rs.450
B]	Humidity Sensor, Wall Mounted type with 3 mtr PVC Cable Model : RH-10 [HSN Code – 90329000] Humidity Range : 20% TO 80% RH , Output : 0 to 3.3 vdc Operating Temp. Range : 45 deg.c max Excitation Voltage : + 5vdc Dimension : 27 [L] x11.9 [W] x6.7 [H]	01 No.	Rs.950
C]	Humidity Sensor, Wall Mounted type with 3 mtr PVC Cable Model : RH-15 [HSN Code – 90329000] Humidity Range : 20% TO 90% RH , Output : 0 to 3 vdc Operating Temp. Range : 60 deg.c max Excitation Voltage : + 5vdc Dimension : 28(L) x 22(W) x 5(D)	01 No	Rs.810
D]	Imported Humidity Sensor with 3 mtr PVC Cable Type : cylindrical , Wall Mounted Type Model RH-20 [HSN Code – 90329000] 0 to 100% rh Range , Accuracy : +/-3% Operating Temp. Range : -20 to + 55 deg.c max , Output :1 to 3.6 vdc Excitation Voltage : +5vdc Dimensions : 59[L] , Dia 10mm	1 No	Rs2560
E]	Imported Humidity sensor with 3 mtr PVC cable Type : cylindrical , Wall Mounted Type Model : RH-35 [HSN Code – 90329000] Humidity range : 0 to 100%rh , Accuracy better than +3% RH Temp. range : -40 to + 85 deg.c Operating voltage : + 5VDC Output : 1 to 3.67 vdc Probe Dimension : 12 mm dia x 75 mm length	1 No	Rs. 7500

COMMERCIAL TERMS & CONDITION

Delivery : 10 days

Payment Terms: 100% Advance along with PO.

Warranty: 1 year for controller & Indicator only

Validity of offer: 30 Days from the dated of offer.

Note :

Thanking you and assuring you of our best attention,

[pion line.com](http://pionline.com)

Freight	At
SGST @ 9%	Actuals
CGST @ 9%	Extra
	Extra

